

RONA

SPECIFICATIONS

MOUNTING		WALL
POWER	[W]	3
LAMP		built-in LED
LUMINOUS FLUX*	[lm]	160
LIGHT COLOUR	[K]	3000
CRI		>80
BEAM ANGLE	[°]	40
AVERAGE LIFETIME	[h]	L80/B50.000
LUMINOUS EFFICACY	[lm/W]	53
POWER SUPPLY	[V] [A]	220-240V AC 50/60 Hz
LED-DRIVER		INCLUDED
DIMMING		NO
THROUGH-WIRING		NO
MATERIAL		ALUMINUM
INGRESS PROTECTION		IP20
PROTECTION CLASS		I
NET WEIGHT	[kg]	1,06
GROSS WEIGHT	[kg]	1,10
COLOUR (HOUSING)		SILVERGREY



LIGHT DISTRIBUTION

n/a

INCLUDING USB PORT FOR DEVICE CHARGING

*Luminous flux values are nominal LED data at a operating temperature of 25° C


OPTIONS / OPTIONAL ACCESSORIES (SMARTPHONE NOT INCLUDED)

Colours




silvergrey

MOUNTING DIMENSIONS



FIXTURE DIMENSIONS



IP20

DLS LIGHTING

www.dslighting.com

***DLS**
LIGHTING